



OAK TVETA

The rich, coffee stain on this single-strip oak floor from the Småland Collection allows the fully smoked, charcoal nuances in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DESCRIPTION

Article Number	151NDSEK04KW240
Surface treatment	Oil
Design features	Bevelled 4-sided, brushed, light smoked, handscraped, saw marks
Dimensions	2420 x 187 x 15 mm
Weight per Package	22 kg
Area per Package	2.72 m ²
Area Per Board	0.453 m ²

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Stained product - noticable color change over time.

FACTS

Wood Species	Oak
Board	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Småland Collection
Resandable	2-4 times
Natural/Stained	Stained
Brinell Value	3, 7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	3, 5 mm
Core material	Pine/Spruce lamella
Backside material	Veneer
Thickness	15 mm
Installation method	Floating, glue-down
EAN Code	7393969039055
Surface Colour	Shadow Brown

TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³		>500 kg/m ³
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m ² K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

CERTIFICATES

